

hauwo



PATIENT SAFETY 4.0

hd 380 WSI-V ValiPak

V.1.0

hd 380 WSI-V ValiPak

VALIDATABLE BAR SEALER.

hd 380 WSI-V ValiPak

The hd 380 WSI-V ValiPak is a validatable, permanently heated bar sealer for pouches and reels (SBS) in doctor's and dentist's surgeries. Thanks to the compact design it is ideal for use in small institutions. As the first sealing system in its class the ValiPak meets the validation requirements.




hd 380 WSI-V

COMPACT DESIGN.

The hd 380 WSI-V is equipped with an integrated roll holder and manual cutting device.

OPERATION.

The sealing process is started by pushing down the hand lever. During the sealing process the packaging material can be cut with the manual cutting device. The cutting length is 250 mm (7.9 inch). Once the sealing time has elapsed, a signal sounds to complete the sealing process.



SAFETY.

Automatic monitoring of the process parameters sealing time, sealing temperature and contact pressure. Display of incorrect parameters on the 7-segment display.



7-segment display

SEAL STRENGTH.

The sealing seam of 9 mm have a high seal strength but also excellent peeling properties without paper shredding, even if the user peels the pack open in the wrong direction.

SUSTAINABILITY.

Maintenance free, without PTFE tape, as well as energy efficient thanks to continuously heated sealing system and stand by function.

FLEXIBILITY.

The sealers are suitable for packaging sealable paper bags (EN ISO 11607-1/ EN 868-4), sealable pouches and reels (EN ISO 11607-1/EN 868-5) made of film and paper according to the EN 868-3.

COMMUNICATION.

The hd 380 WSI-V ValiPak can easily be linked to batch documentation and tracking systems via the RS 232 interfaces.



PACKAGING, LABELLING AND DOCUMENTING SYSTEM.

The hd 380 WSI-V ValiPak can be extended to a packaging labelling and documenting system with the optional 2D barcode scanner (IntelligentScan Technology) and the ValiPrint label printer. Regardless of whether it's sealable pouches or reels, wrappable sterilization sheets or reusable containers, this system assists medical professionals meet the packaging inspection and labelling requirements. No additional computer peripheral equipment is required to scan important packaging information and print it onto a label.

hd 380 WSI-V ValiPak

RANGE OF USE AND CERTIFICATIONS

Especially suitable for use in clinics, doctors and dentists clinics, doctors and dentists	x
--	---

POWER SUPPLY DATA

Mains connection	115/230 V
Mains frequency	50/60 HZ
Power (may vary during heat-up time)	100 W

TECHNICAL DATA

Dimensions w x d x h	420 x 360 x 220 mm (16.5 x 14.2 x 8.7 inch)
Weight	6.1 kg / 13.4 lbs.
Sealing system	constantly heated
casing cover	Stainless steel AISI 304
Integrated roll holder	x
Sealing seam length	250 mm (9.8 inch)
Integrated cutter	x
Cutting length	250 mm (9.8 inch)
Sealing seam width	9 mm ± 1 mm (0.35 ± 0.04 inch)
Heat-up time	approx. 2 min

SEALING MATERIALS

Sealable paper pouches according to EN ISO 11607-1/EN 868-4	x
Sealable pouches and reels according to EN ISO 11607-1/EN 868-5 made of film and paper according to EN 868-3	x

ELECTRONIC AND COMMUNICATION

Validatable process	x
Display	7-segment display
PC interfaces	2 x RS 232

PROCESS VARIABLES AND PARAMETERS

Sealing temperature	fix 190 °C (374 °F) (monitored)
Contact pressure	fix (monitored)
Sealing time	3 s (monitored)

ACCESSORIES

InkTest / InkTest PRO (dye penetration test)	x
Seal Check dent	x
Extendable tray (for comfortable working even at desk edges)	x
Scanner (IntelligentScan)	x
Label Printer ValiPrint	x

Technical modifications reserved
07/2021 | 9.343.040



hawo GmbH
Obere Au 2-4
74847 Obrigheim
Germany
T +49 (0) 6261/9770-0
F +49 (0) 6261/9770-69
info@hawo.com
www.hawo.com

hawo USA:
hawo
150 North Michigan Avenue
35th Floor
Chicago, Illinois 60601
T +1 312 585 8329
F +1 312 644 0738
info@hawo-usa.com
www.hawo-usa.com

hawo ASIA:
hawo
25 International Business Park
#03-105 German Centre
Singapore 609916
T +65 6433 5339
F +65 6433 5359
info@hawo-asia.com
www.hawo-asia.com

Follow us:

